BURNS MANUFACTURING, INC



Part# 7848

Automatic Flush Bolt with Bottom Fire Bolt - Metal Door

3 Hour Fire Rating - Metal Doors

Size	Top Bolt: 1" × 6-3/4" Bottom Fire Bolt: 1" x 1-25/32" face plate - Drill 7/8" diameter hole in inactive door, 1" diameter hole in active door
Finishes	US3/605 – Bright Brass US4/606 – Satin Brass US10B/613 – Dark Bronze US32/629 – Bright Stainless Steel US32D/630 – Satin Stainless Steel
Material	Brass or Stainless Steel
Features	UL Listed Single Non-Handed Automatic Top Flush Bolt for Metal Door with Bottom Fire Bolt. Bottom Fire Bolt eliminates the bottom automatic flush bolt and dust proof strike. BFB projects a bolt when subjected to 230 degrees F - locking the leaves together.

Copyright ©2026 Burns Manufacturing Inc. All rights reserved.
Reproduction in whole or in part without the express written permission of Burns Manufacturing Inc. is prohibited.

2001 Lowell Avenue, Erie, PA 16506
Phone: 800.519.2610 • Fax: 800.432.8767
Website: www.burnsmfg.com
Email: burnsmfg@burnsmfg.com